BEF HOME
fire for your heart

SPECIFICATIONS

Rated thermal input	3,8 kW
Efficiency	86 %
Smoke flue diameter	150 mm
Min. thrust (under pressure) for rated thermal input	12 Pa
Fuel gas temperature	193 °C
Volume of fuel gas	3 g/s
CO emissions in fuel gas (at 13 % O_2)	0,0814 %
Dust in the fuel gas (at 13 % O_2)	16 mg/Nm^3
Volume of fuel per hour	1,15 kg/h
Fuel	wood (beech logs)
Weight	112 kg

LIST OF SPARE PARTS

Glass



530 x 330 x 468 mm

Carcon stones

1. Front bottom
2. Back bottom
3. Back
4. Side
5. Deflector



BEF PASSIVE 6 CL

BLOWER DOOR TEST | ČSN EN 16510 | eco design

www.befhome.com

BeF Home s. r. o. I Kotvrdovice 277, 679 07 Kotvrdovice I tel.: +420 516 428 240 I email: obchodnik@bef.cz

BEF HOME
fire for your heart

TECHNICAL DRAWING



BEF PASSIVE 6 CL

BLOWER DOOR TEST | ČSN EN 16510 | eco design

www.befhome.com

BeF Home s. r. o. I Kotvrdovice 277, 679 07 Kotvrdovice I tel.: +420 516 428 240 I email: obchodnik@bef.cz